


A waterproof recessed lighting profile.

LightLine SEAL is a water-proof IP65 lighting fixture with unique seals which allows its installation in rough environmental conditions. The fixture's wide opal light diffuser delivers a light distribution that is comfortable for the eyes. Available in a variety of intensities and power supply options to suit any length requirements and ceiling heights. Can also be installed as a continuous light strip with a customized frame.

Ideal for laboratories, clinics, showers, toilets, kitchens and more.

Technical specifications:



Material: Anodized Aluminium. Coated or Coloured by choice.

Diffuser: Opal

Body Colour: • Additional colours by special order.

Power: Up to 25W/m

CCT: 2700K / 3000K / 4000K **Mounting Type:** Recessed.


Max Length per Feed: Up to 5 m' for 15W/m model.

Up to 3 m' for 25W/m

Power (W)	CCT	Width×Height (mm)	Diffuser	Luminaire's Lumen Output (lm)
10	4000K	79×80	Opal	600
15	4000K	79×80	Opal	855
25	4000K	79×80	Opal	1,425

^{*} Data shown is for a few of the available models. The luminaires are available in different colour temperatures, optics, lumen outputs and power. ** Tolerance: -+10%.

Photometric Curves:



EH-VS LICHTLINE SEAL.

























▶ 32